

## PIPE SPECIFICATIONS

| NOM Pipe Size | OD in Inches | Schedule   |        |        |        |        |        |        |        |
|---------------|--------------|------------|--------|--------|--------|--------|--------|--------|--------|
|               |              | Data       | 10     | STD    | 40     | XH     | 80     | 160    | XXH    |
| 1/8"          | 0.405"       | Wall Thick | 0.049  | 0.068  |        | 0.095  |        | -      | -      |
|               |              | lb/ft      | 0.19   | 0.24   |        | 0.31   |        | -      | -      |
| 1/4"          | 0.540"       | Wall Thick | 0.065  | 0.088  |        | 0.119  |        | -      | -      |
|               |              | lb/ft      | 0.33   | 0.43   |        | 0.54   |        | -      | -      |
| 3/8"          | 0.675"       | Wall Thick | 0.065  | 0.091  |        | 0.126  |        | -      | -      |
|               |              | lb/ft      | 0.42   | 0.57   |        | 0.74   |        | -      | -      |
| 1/2"          | 0.840"       | Wall Thick | 0.083  | 0.109  |        | 0.147  |        | 0.188  | 0.294  |
|               |              | lb/ft      | 0.67   | 0.85   |        | 1.09   |        | 1.31   | 1.72   |
| 3/4"          | 1.050"       | Wall Thick | 0.083  | 0.113  |        | 0.154  |        | 0.219  | 0.308  |
|               |              | lb/ft      | 0.86   | 1.13   |        | 1.48   |        | 1.95   | 2.44   |
| 1"            | 1.315"       | Wall Thick | 0.109  | 0.133  |        | 0.179  |        | 0.250  | 0.358  |
|               |              | lb/ft      | 1.41   | 1.68   |        | 2.17   |        | 2.85   | 3.66   |
| 1 1/4"        | 1.660"       | Wall Thick | 0.109  | 0.140  |        | 0.191  |        | 0.250  | 0.382  |
|               |              | lb/ft      | 1.81   | 2.27   |        | 3.00   |        | 3.77   | 5.22   |
| 1 1/2"        | 1.900"       | Wall Thick | 0.109  | 0.145  |        | 0.200  |        | 0.281  | 0.400  |
|               |              | lb/ft      | 2.09   | 2.72   |        | 3.63   |        | 4.86   | 6.41   |
| 2"            | 2.375"       | Wall Thick | 0.109  | 0.154  |        | 0.218  |        | 0.344  | 0.436  |
|               |              | lb/ft      | 2.64   | 3.66   |        | 5.03   |        | 7.47   | 9.04   |
| 2 1/2"        | 2.875"       | Wall Thick | 0.120  | 0.203  |        | 0.276  |        | 0.375  | 0.552  |
|               |              | lb/ft      | 3.53   | 5.80   |        | 7.67   |        | 10.02  | 13.71  |
| 3"            | 3.500"       | Wall Thick | 0.120  | 0.216  |        | 0.300  |        | 0.438  | 0.600  |
|               |              | lb/ft      | 4.34   | 7.58   |        | 10.26  |        | 14.34  | 18.60  |
| 3 1/2"        | 4.000"       | Wall Thick | 0.120  | 0.226  |        | 0.318  |        | -      | 0.636  |
|               |              | lb/ft      | 4.98   | 9.12   |        | 12.52  |        | -      | 22.87  |
| 4"            | 4.500"       | Wall Thick | 0.120  | 0.237  |        | 0.337  |        | 0.531  | 0.674  |
|               |              | lb/ft      | 5.62   | 10.80  |        | 15.00  |        | 22.53  | 27.57  |
| 5"            | 5.563"       | Wall Thick | 0.134  | 0.258  |        | 0.375  |        | 0.625  | 0.750  |
|               |              | lb/ft      | 7.78   | 14.63  |        | 20.80  |        | 32.99  | 38.59  |
| 6"            | 6.625"       | Wall Thick | 0.134  | 0.280  |        | 0.432  |        | 0.719  | 0.864  |
|               |              | lb/ft      | 9.30   | 18.99  |        | 28.60  |        | 45.39  | 53.21  |
| 8"            | 8.625"       | Wall Thick | 0.148  | 0.322  |        | 0.500  |        | 0.906  | 0.875  |
|               |              | lb/ft      | 13.41  | 28.58  |        | 43.43  |        | 74.76  | 72.49  |
| 10"           | 10.750"      | Wall Thick | 0.165  | 0.365  |        | 0.500  | 0.594  | 1.125  | 1.000  |
|               |              | lb/ft      | 18.67  | 40.52  |        | 54.79  | 64.49  | 115.75 | 104.23 |
| 12"           | 12.750"      | Wall Thick | 0.180  | 0.375  | 0.406  | 0.500  | 0.688  | 1.312  | 1.000  |
|               |              | lb/ft      | 24.19  | 49.61  | 53.57  | 65.48  | 88.71  | 160.42 | 125.61 |
| 14"           | 14.000"      | Wall Thick | 0.250  | 0.375  | 0.438  | 0.500  | 0.750  | 1.406  | -      |
|               |              | lb/ft      | 36.75  | 54.62  | 63.50  | 72.16  | 106.23 | 189.29 | -      |
| 16"           | 16.000"      | Wall Thick | 0.250  | 0.375  | 0.500  | 0.500  | 0.844  | 1.594  | -      |
|               |              | lb/ft      | 42.09  | 62.64  | 82.85  | 82.85  | 136.74 | 245.48 | -      |
| 18"           | 18.000"      | Wall Thick | 0.250  | 0.375  | 0.562  | 0.500  | 0.938  | 1.781  | -      |
|               |              | lb/ft      | 47.44  | 70.65  | 104.76 | 93.54  | 171.08 | 308.79 | -      |
| 20"           | 20.000"      | Wall Thick | 0.250  | 0.375  | 0.594  | 0.500  | 1.031  | 1.969  | -      |
|               |              | lb/ft      | 52.78  | 78.67  | 123.23 | 104.23 | 209.06 | 379.53 | -      |
| 22"           | 22.000"      | Wall Thick | 0.250  | 0.375  | -      | 0.500  | 1.125  | 2.125  | -      |
|               |              | lb/ft      | 58.13  | 86.68  | -      | 114.92 | 251.05 | 451.49 | -      |
| 24"           | 24.000"      | Wall Thick | 0.250  | 0.375  | 0.688  | 0.500  | 1.219  | 2.344  | -      |
|               |              | lb/ft      | 63.47  | 94.71  | 171.45 | 125.61 | 296.86 | 542.64 | -      |
| 26"           | 26.000"      | Wall Thick | 0.312  | 0.375  | -      | 0.500  | -      | -      | -      |
|               |              | lb/ft      | 85.68  | 102.72 | -      | 136.60 | -      | -      | -      |
| 30"           | 30.000"      | Wall Thick | 0.312  | 0.375  | -      | 0.500  | -      | -      | -      |
|               |              | lb/ft      | 119.02 | 118.76 | -      | 157.68 | -      | -      | -      |
| 36"           | 36.000"      | Wall Thick | -      | 0.375  | 0.750  | 0.500  | -      | -      | -      |
|               |              | lb/ft      | -      | 142.81 | 282.62 | 189.75 | -      | -      | -      |
| 42"           | 42.000"      | Wall Thick | -      | 0.375  | -      | 0.500  | -      | -      | -      |
|               |              | lb/ft      | -      | 166.86 | -      | 221.82 | -      | -      | -      |
| 48"           | 48.000"      | Wall Thick | -      | 0.375  | -      | 0.500  | -      | -      | -      |
|               |              | lb/ft      | -      | 190.92 | -      | 253.86 | -      | -      | -      |